



FORGE

stainless steel 300 round shower head

20004010595



INSTALLATION GUIDELINES

- 1. Installation should be carried out by a competent engineer, in accordance with water regulations.
- Before installation, ensure supply pipes are flushed clean. Debris or loose particles will affect the efficiency of the shower head. Failure to flush through pipe work before installation of taps may cause serious damage to the shower head for which bathstore will not be liable.
- 3. Shower heads in hard water areas. To prolong the lifespan and reduce servicing periods we recommend that a suitable water softener be fitted.

CARE AND MAINTENANCE:

To maintain the appearance of this product, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Any other cleaning action will invalidate your warranty.

Abrasive cleaners, scouring cleaners and acidic cleaners **must not be used** under any circumstances. Avoid contact with all solvents (including chlorinated solvents, ketones or acetones as these may result in surface deterioration or etching). Also avoid contact with any harsh household chemicals such as oven cleaners, drain cleaners, rust removers, paint strippers and toilet bowl cleaners, bar keepers friend, brasso or similar products.

DIMENSIONS:

Diameter 300mm

FEATURES AND BENEFITS

- Highest quality stainless steel
- Contemporary Italian design
- Lead free

FLOW RATE & OPERATING CONDITIONS

DIMENSION & LINE DRAWING

Recommended water pressure 1 – 4 bar Optimum water pressure 3 bar

1 bar	15 L/Min
2 bar	20 L/Min
3 bar	22 L/Min
4 bar	25 L/Min



1



FORGE

stainless steel 200 ceiling arm

20004010600



DIMENSIONS:

Length of the arm

200mm

FEATURES AND BENEFITS

- Highest quality stainless steel
- All products are lead free

INSTALLATION GUIDELINES

- 1. Installation should be carried out by a competent engineer, in accordance with water regulations.
- Ensure the ceiling is strong enough to support the shower head
- 3. Mark the ceiling before drilling
- 4. Be aware of the location of pipes and cables behind the wall before drilling.

CARE AND MAINTENANCE:

To maintain the appearance of this product, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Any other cleaning action will invalidate your warranty.

Abrasive cleaners, scouring cleaners and acidic cleaners **must not be used** under any circumstances. Avoid contact with all solvents (including chlorinated solvents, ketones or acetones as these may result in surface deterioration or etching). Also avoid contact with any harsh household chemicals such as oven cleaners, drain cleaners, rust removers, paint strippers and toilet bowl cleaners, bar keepers friend, brasso or similar products.

DIMENSION & DRAWING

