

NOIR

300 round shower head matt black

20004010880



DIMENSIONS:

Diameter 300mm

FLOW RATE & OPERATING CONDITIONS

Recommended water pressure 1 – 4 bar Optimum water pressure 3 bar

| 1 bar | 15 L/Min |
|-------|----------|
| 2 bar | 20 L/Min |
| 3 bar | 22 L/Min |
| 4 bar | 25 L/Min |

INSTALLATION GUIDELINES


- Installation should be carried out by a competent engineer, in accordance with water regulations.
- Before installation, ensure supply pipes are flushed clean.
 Debris or loose particles will affect the efficiency of the shower
 head. Failure to flush through pipe work before installation of
 taps may cause serious damage to the shower head for which
 bathstore will not be liable.
- Shower heads in hard water areas. To prolong the lifespan and reduce servicing periods we recommend that a suitable water softener be fitted.


CARE AND MAINTENANCE:

To maintain the appearance of this product, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Any other cleaning action will invalidate your warranty.

Abrasive cleaners, scouring cleaners and acidic cleaners **must not be used** under any circumstances. Avoid contact with all solvents (including chlorinated solvents, ketones or acetones as these may result in surface deterioration or etching). Also avoid contact with any harsh household chemicals such as oven cleaners, drain cleaners, rust removers, paint strippers and toilet bowl cleaners, bar keepers friend, brasso or similar products.

DIMENSION & LINE DRAWING







NOIR

Wall Arm matt black

20004010870



DIMENSIONS:Length of the body

Length of the body 400mm

INSTALLATION GUIDELINES

- Installation should be carried out by a competent engineer, in accordance with water regulations.
- 2. Ensure the wall is strong enough to support the shower arm.
- 3. Mark the wall before drilling
- Be aware of the location of pipes and cables behind the wall before drilling
- 5. Use the appropriate drill bit for the wall plug.

CARE AND MAINTENANCE:

To maintain the appearance of this product, ensure that it is regularly cleaned only using a clean, soft damp cloth. A solution of warm water and a mild detergent may be used where necessary, and then the fitting rinsed thoroughly and wiped dry. Any other cleaning action will invalidate your warranty.

Abrasive cleaners, scouring cleaners and acidic cleaners **must not be used** under any circumstances. Avoid contact with all solvents (including chlorinated solvents, ketones or acetones as these may result in surface deterioration or etching). Also avoid contact with any harsh household chemicals such as oven cleaners, drain cleaners, rust removers, paint strippers and toilet bowl cleaners, bar keepers friend, brasso or similar products.

DIMENSION & LINE DRAWING

